

# Floor Standing A Series



(Manual) (Auto)

\* Optional  
 \*\* RR100/125/140DX/1  
 RQ100/125/140DX/1



- > Stylish profile with classy control panel
- > Dual control, settings by pressing control panel or wireless handset
- > Long air throw distance of up to 25m (size 140)
- > Keylock function
- > Wireless handset BRC52A61 (H/P) or BRC52A62 (C/O) is supplied as standard

FVRN71/100/125/140AXV1  
 FVQN71/100/125/140AXV1



RR71CXV1/RR71CXV1  
 RQ71CXV1



RR100/125/140DX/1  
 RQ100/125/140DX/1

## Specification for Floor Standing, Cooling only

Indoor Model Name		FVRN71AXV1	FVRN71AXV1	FVRN100AXV1	FVRN125AXV1	FVRN140AXV1	
Outdoor Model Name		RR71CXV1	RR71CXV1	RR100DX/1	RR125DX/1	RR140DX/1	
Nominal Cooling Capacity	Btu/h	28000	28000	40000	45000	55000	
	kW	8.21	8.21	11.72	13.19	16.12	
Nominal EER	W/W	2.89	2.89	2.89	2.82	2.94	
	Btu/h	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	
Indoor	Power Supply	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	
	Air Flow	cfm	675/625/530	675/625/530	1035/945/845	1035/935/835	1170/1085/985
	Sound Pressure Level	dBA	44/42/39	44/42/39	49/47/44	50/48/46	54/53/51
	Height	mm	1850	1850	1850	1850	1850
	Width	mm	600	600	600	600	600
	Depth	mm	270	270	350	350	350
	Net Weight	kg	42	42	45	48	51
	Power Supply	V/Ph/Hz	220-240/1/50	380-415/3/50	380-415/3/50	380-415/3/50	380-415/3/50
Outdoor	Sound Pressure Level	dBA	58	58	58	60	65
	Height	mm	753	753	852	852	852
	Width	mm	855	855	1030	1030	1030
	Depth	mm	328	328	400	400	400
	Net Weight	kg	57	57	95	98	105
	Pipe Connection- Liquid	mm	9.52	9.52	9.52	9.52	9.52
	Pipe Connection- Gas	mm	15.88	15.88	15.88	15.88	19.05
	Max. Allowable Length	m	45	45	45	45	45
Max. Allowable Elevation	m	25	25	25	25	25	

## Specification for Floor Standing, Cooling and Heating

Indoor Model Name		FVQN71AXV1	FVQN100AXV1	FVQN125AXV1	FVQN140AXV1	
Outdoor Model Name		RQ71CXV1	RQ100DX/1	RQ125DX/1	RQ140DX/1	
Nominal Cooling Capacity	Btu/h	28000	40000	45000	55000	
	kW	8.21	11.72	13.19	16.12	
Nominal EER	W/W	2.89	2.89	2.82	2.94	
	Btu/h	27500	42000	46000	54500	
Nominal Heating Capacity	kW	8.06	12.31	13.48	16.00	
	W/W	3.20	3.14	3.02	3.01	
Indoor	Power Supply	V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
	Air Flow	cfm	675/625/530	1035/945/845	1035/935/835	1170/1085/985
	Sound Pressure Level	dBA	44/42/39	49/47/44	50/48/46	54/53/51
	Height	mm	1850	1850	1850	1850
	Width	mm	600	600	600	600
	Depth	mm	270	350	350	350
	Net Weight	kg	42	45	48	51
	Power Supply	V/Ph/Hz	220-240/1/50	380-415/3/50	380-415/3/50	380-415/3/50
Outdoor	Sound Pressure Level	dBA	58	58	60	65
	Height	mm	753	852	852	852
	Width	mm	855	1030	1030	1030
	Depth	mm	328	400	400	400
	Net Weight	kg	57	95	98	105
	Pipe Connection- Liquid	mm	9.52	9.52	9.52	9.52
	Pipe Connection- Gas	mm	15.88	15.88	15.88	19.05
	Max. Allowable Length	m	45	45	45	40
Max. Allowable Elevation	m	25	25	25	20	